



FlashGard Thru-wall Flashing

Firestone Item Number

W56TW41205:	30.48 cm x 15.24 m (12" x 50')
W56TW41605:	40.64 cm x 15.24 m (16" x 50')
W56TW41805:	45.72 cm x 15.24 m (18" x 50')
W56TW42005:	50.80 cm x 15.24 m (20" x 50')
W56TW42405:	60.96 cm x 15.24 m (24" x 50')
W56TW43605:	91.44 cm x 15.24 m (36" x 50')

DESCRIPTION:

Firestone's FlashGard Thru-Wall Flashing membrane is a flexible EPDM membrane that forms a moisture retarder in cavity wall construction by directing water to a building's exterior.

PREPARATION OF SUBSTRATES:


1. Substrates must be clean, dry, smooth, and free of sharp edges, fines, loose or foreign materials, oil, grease, and other materials that may damage the geomembrane.
2. All roughened surfaces that can damage the geomembrane shall be repaired as specified to offer a smooth substrate.
3. All substrate voids greater than 6.3 mm (0.25") wide shall be properly filled with an acceptable fill material.

METHOD OF APPLICATION:

Firestone's FlashGard Thru-Wall Flashing membrane must be installed in accordance with current Firestone Specialty Products specifications and details.

STORAGE:

1. Store away from sources of punctures and physical damage.
2. Store away from ignition sources as geomembrane will burn when exposed to open flame.



PRODUCT DATA

<u>Property</u>	<u>Test Method</u>	<u>Typical Values</u>
Tensile Strength:	ASTM D-412 (Die C)	9.0 MPa (1305 psi)
Elongation:	ASTM D-412 (Die C)	300%
Tear Resistance:	ASTM D-624 (Die C)	26.3 kN/m (150 lbf/in)
Ozone Resistance:	ASTM D-1140	No Cracks
166 hrs/100 pphm @ 37.8°C (104°F) with 50% extension		
Heat Aging:	ASTM D-573	
29 days @ 116°C (240°F)		
Tensile Strength:	ASTM D-412	8.3 MPa (1205 psi)
Elongation:	ASTM D-412	200%
Brittleness Temp:	ASTM D-2137	-45° C (-49° F)
Water Absorption:	ASTM D-471	+8, -2
change in weight after immersion in water for 166 hrs @ 70°C (158°F)		
Water Vapor Permeability:	ASTM E-96	2.0 Perm mils

PACKAGING:

<u>Thickness</u>	<u>Widths</u>	<u>Lengths</u>	<u>Rolls Per Box</u>
1.02 mm (0.040")	30.48 cm (12.0")	15.24 m (50.0')	2 rolls
1.02 mm (0.040")	40.64 cm (16.0")	15.24 m (50.0')	1 roll
1.02 mm (0.040")	45.72 cm (18.0")	15.24 m (50.0')	1 roll
1.02 mm (0.040")	50.80 cm (20.0")	15.24 m (50.0')	1 roll
1.02 mm (0.040")	60.96 cm (24.0")	15.24 m (50.0')	1 roll
1.02 mm (0.040")	91.44 cm (36.0")	15.24 m (50.0')	1 roll

PRECAUTIONARY DATA:

1. Take care when moving, transporting, handling, etc. to avoid sources of punctures and physical damage.
2. Refer to Material Safety Data Sheets (MSDS) for safety information.

LEED INFORMATION:

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Locations:	Prescott, AR Kingstree, SC

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone Specialty Products
250 West 96th Street, Indianapolis, Indiana 46260
Specialty Products (800) 428-4442
Internet Address: <http://www.firestonesp.com>