

TECHNICAL INFORMATION SHEET

FSP-223
11/07/2008



FlashGard™ Adhesive Tape



Firestone Item Number:

W56RAC1699: 15.2 m (50' rolls)

DESCRIPTION:

Firestone FlashGard Adhesive Tape is designed for splicing of FlashGard membrane panels and for attaching FlashGard membrane to substrates.

METHOD OF APPLICATION:

1. Ensure FlashGard membrane surface is clean prior to application.
2. If necessary, wipe membrane with a clean cotton rag, using unleaded gas or denatured alcohol.
3. Apply Firestone 7877 Spray Adhesive Primer to membrane and substrate surfaces.
4. After application, allow solvents to flash off before mating. Use touch-push test to verify if solvents have flashed off; adhesive is ready to be bonded if pushing on adhesive with a clean dry finger reveals no stringing or movement of the adhesive layer. Open time usually ranges from 5 to 30 minutes.
5. These instructions are general in nature; refer to Firestone Specialty Products' FlashGard Thru-Wall Flashing specifications and details for specifics.

SHELF LIFE:

1. Shelf life of one (1) year can be expected if stored in original sealed containers at temperatures between 15.6 - 26.7° C (60 - 80° F). If exposed to lower temperatures, restore to room temperature prior to use.
2. Shelf life will be shortened if exposed to elevated temperatures.
3. Rotate stock to ensure stored material will not go beyond the shelf life of one (1) year.

PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
Base:	Butyl Polymer
Color:	Black
Solvents:	None
Solids:	100%
Specific Gravity:	1.15 - 1.25 (H2O = 1)
Cure State:	Cured
Thickness:	1.588 mm (0.0625")
Width:	38.1 mm (1.5")
Length:	5.2 m (50.0')

Physical Characteristics

1. Excellent moisture resistance.
2. Excellent resistance to heat and cold.
3. Excellent green tack.
4. Tape is wound on release paper to facilitate handling.

STORAGE:

1. Store in original unopened containers at temperatures between 15.6 - 26.7° C (60 - 80° F) until ready for use.
2. Do not store on job site in direct sunlight or at temperatures above 26.7° C (80°F).

PACKAGING:

5.2 m (50') rolls, 4 rolls per carton, 88 cartons per pallet.

PRECAUTIONARY DATA:

Review Material Safety Data Sheet (MSDS) prior to use.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Michigan Center, MI

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone Specialty Products
250 West 96th Street, Indianapolis, Indiana 46260
Specialty Products (800) 428-4442
Internet Address: <http://www.firestonesp.com>

S723-SPP-076