

Glass Block - DECORA®

Premiere Series Glass Block



PITTSBURGH CORNING™

Product Description

Distinctive wavy undulations of this pattern provide maximum light transmission with subtle visual distortion. The non-directional faces make installation quick.

Nominal Size (Actual size is 1/4" less than nominal; mm shown is actual)	Weight (lb/ft²) installed with mortar	Heat Transmission U Value (Btu/hr ft² °F)	Thermal Resistance R Value (hr ft² °F/Btu)	Visible Light Transmission (%)	Shading Coef.	Sound Transmission S.T.C.	Solar Heat Gain Coefficient
Standard Premiere Series Block – Nominal Thickness = 4"; Actual Thickness = 3-7/8" (98mm)							
6" x 6" (146mm)	20	0.51	1.96	75	0.65	37	.66-.68
8" x 8" (197mm)	20	0.51	1.96	75	0.65	39	.66-.68
12" x 12" (299mm)	20	0.51	1.96	75	0.65	35	.66-.68
4" x 8" (95 x 197mm)	20	0.51	1.96	75	0.65		.66-.68
6" x 8" (146 x 197mm)	20	0.51	1.96	75	0.65		.66-.68

For technical assistance call us toll free at 1-800-659-4731.

MASONPRO, Inc., 43300 Seven Mile Road • Northville, MI 48167 • 800-659-4731 • Fax: 248-347-1670
 Visit our website at www.masonpro.com