

# Glass Block - DECORA®

## THICKSET® - High Performance Line



PITTSBURGH CORNING™

### Product Description

The thicker-faced blocks offer an extra reduction in sound transmission and increased fire resistance available in 60 or 90-minute ratings. The DECORA® pattern provides maximum light transmission with subtle visual distortion. The non-directional faces make installation quick.

- THICKSET® 60 Block DECORA® Pattern provides 60-minute fire rating.
- THICKSET® 90 Block DECORA® Pattern provides 90-minute fire rating.

Nominal Size (Actual size is 1/4" less than nominal; mm shown is actual)	Weight (lb/ft²) installed with mortar	Heat Transmission U Value (Btu/hr ft² °F)	Thermal Resistance R Value (hr ft² °F/Btu)	Visible Light Transmission (%)	Shading Coef.	Sound Transmission S.T.C.	Solar Heat Gain Coefficient
<b>THICKSET® Block – Nominal Thickness = 4"; Actual Thickness = 3-7/8" (98mm)</b>							
<b>THICKSET® 60 Block DECORA® Pattern</b>							
8" x 8" (197mm)	25	0.51	1.96	49	0.65	48	.66-.68
<b>THICKSET® 90 Block DECORA® Pattern</b>							
8" x 8" (197mm)	30	0.51	1.96	38	0.65	50	.66-.68

**For technical assistance call us toll free at 1-800-659-4731.**

MASONPRO, Inc., 43300 Seven Mile Road • Northville, MI 48167 • 800-659-4731 • Fax: 248-347-1670  
 Visit our website at [www.masonpro.com](http://www.masonpro.com)