

Glass Block - VUE®

Premiere Series Glass Block



PITTSBURGH CORNING™

Product Description

Faces are smooth and undistorted to transmit the most light and allow ultimate visibility. This is the best choice for passive solar collection and visual clarity.

Nominal Size (Actual size is 1/4" less than nominal; mm shown is actual)	Weight (lb/ft ²) installed with mortar	Heat Transmission U Value (Btu/hr ft ² °F)	Thermal Resistance R Value (hr ft ² °F/Btu)	Visible Light Transmission (%)	Shading Coef.	Sound Transmission S.T.C.	Solar Heat Gain Coefficient
Standard Premiere Series Block – Nominal Thickness = 4"; Actual Thickness = 3-7/8" (98mm)							
6" x 6" (146mm)	20	0.51	1.96	75	0.65	37	.66-.68
8" x 8" (197mm)	20	0.51	1.96	75	0.65	39	.66-.68
12" x 12" (299mm)	20	0.51	1.96	75	0.65	35	.66-.68
4" x 8" (95 x 197mm)	20	0.51	1.96	75	0.65	-	.66-.68
6" x 8" (146 x 197mm)	20	0.51	1.96	75	0.65	-	.66-.68

For technical assistance call us toll free at 1-800-659-4731.

MASONPRO, Inc., 43300 Seven Mile Road • Northville, MI 48167 • 800-659-4731 • Fax: 248-347-1670
 Visit our website at www.masonpro.com