








## Product Specifications for Tyvek® HomeWrap®

MASONPRO, Inc.  
43300 Seven Mile Road  
Northville, MI 48167  
1-800-659-4731

PROPERTIES	METHOD	TYVEK® HOMEWRAP®
<b>Air Penetration</b>	Air-Ins (cfm/ft <sup>2</sup> @75 Pa)	.007
	Gurley Hill (TAPPI T-460) (sec/100cc)	300
	ASTM E-1677	Type 1
<b>Water Vapor Transmission</b>	ASTM E-96 Method B (g/m <sup>2</sup> -24 hrs) (perms)	400 58
	<b>Water Penetration Resistance</b>	AATCC-127 (cm)
<b>Basis Weight</b>	TAPPI T-41D (oz/yd <sup>2</sup> )	1.8
<b>Breaking Strength</b>	ASTM D-882 Method A (lbs/in)	30/30
<b>Tear Resistance (trapezoid)</b>	ASTM D-1117 (lbs)	6/6
<b>Surface Burning Characteristics</b>	ASTM E-84-97a Flame Spread	Class A
	Indexed Smoke Developed Value	Class A

**WARNING:** Tyvek® is combustible and should be protected from a flame and other high heat sources. If the temperature of Tyvek® reaches 750 F (400 C), it will burn and the fire may spread and fall away from the point of ignition.

For more information:

1-800-44-TYVEK®  
www.tyvekconstruction.com




**Tyvek® HomeWrap®**

Build it once, build it right.