

1585CW®-P2

SHEATHING TAPE



Venture Tape® 1585CW®-P2 is a printed polypropylene sheathing tape coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all interior and exterior sheathing materials.

Venture Tape® 1585CW®-P2 exceeds most building code requirements and can be used for new construction as well as repair on all vapor barrier materials.

CCMC approved, Venture Tape® 1585CW®-P2 is the highest performing, highest value product on the market today.

FEATURES & BENEFITS

- High performance sheathing tape installs and performs well over a wide temperature range
- Excellent vapor barrier tape on polyethylene film
- Performs well as a seam tape on extruded foam products such as **Styrofoam®** and **Foamular®**
- Applies to all major housewraps including **Tyvek®** and **Typar®**
- Great for use as a sealing tape on **DensGlass Gold®** and other sheathing brands

PRODUCT CONFIGURATIONS

- 60mm x 66m
- 20 rolls/case

MASONPRO, Inc.
Northville, MI 48167
1-800-659-4731
www.masonpro.com

Test	Typical Value	Test Method
Total Product Thickness	3.0 mils	PSTC-133
Carrier Thickness	1.5 mils	PSTC-133
Adhesive Thickness	1.5 mils	PSTC-133
Peel Adhesion - Stainless Steel	65 oz/in	PSTC-133
Peel Adhesion - Polyethylene	16 oz/in	PSTC-133
Peel Adhesion - Tyvek®	28 oz/in	PSTC-133
Shear Strength	>96 hours	PSTC-133
Tensile Strength	20 lb/inch width	PSTC-133
Elongation	136%	PSTC-133
WVTR	0.16 g/100 in ² /24 hr	ASTM E-96
Application Temperature	-20° F to 120° F	
Service Temperature	-40° F to 275° F	

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

VentureTape®