

ARVRON, INC. STEER-O-CELL[®]

MATERIAL SAFETY DATA SHEET

I-PRODUCT INFORMATION

PRODUCT: ARVRON, INC.
STEER-O-CELL[®] MODIFIED

SYNONYMS: EPS, Expanded Polystyrene

PRODUCT GRADES: Type I, VIII, II and IX

CHEMICAL FAMILY: Polystyrene Thermoplastic Polymer

CAS REGISTRY NO: 9003-53-6

CAS NAME: Benzene, Ethenyl-Homopolymer

FORMULA: (C₈H₈)_x

TSCA INVENTORY STATUS: Listed

HAZARD RATING: 2 = Moderate		HEALTH	0
0 = Minimal	3 = Serious	FIRE	2
1 = Slight	4 = Severe	REACTIVITY	0

CONTACT: ARVRON, INC.
4720 Clay S.W.
Grand Rapids, MI 49548
(616) 530-1888

II-INGREDIENTS

HAZARDOUS COMPONENTS:	CAS REGISTRY NO:	APPROX. WEIGHT PERCENTAGE
Pentane	109-66-0	Less Than 2%

NON-HAZARDOUS COMPONENTS	CAS REGISTRY NO:	APPROX. WEIGHT PERCENTAGE
Polystyrene	9003-53-6	98% Min.

III-PHYSICAL DATA

FORM: Rigid Cellular Foam Blocks, Boards & Shapes

COLOR: White

ODOR: Very Slight Hydrocarbon Odor

BOILING POINT: N/A

Melting Point: Softens at 175° to 220°

SPECIFIC GRAVITY: [Water = 1]: Density 0.6PCF to 2.0PCF

VAPOR PRESSURE: N/A

VOLATILES BY VOLUME: Less than 4% Pentane & Water

VAPOR DENSITY: (AIR = 1): N/A

EVAPORATION RATE: None

SOLUBILITY IN WATER: Insoluble

IV-FIRE & EXPLOSION DATA

FLASH POINT, AND METHOD USED: 610°F Min. [ASTM D 1929]

SPECIAL FIRE FIGHTING INSTRUCTIONS: Use approved self-contained breathing apparatus respirator and approved Personal Protective Clothing.

EXTINGUISHING MEDIA: Water Fog, Carbon Dioxide, Foam and Dry Chemical

AUTOIGNITION TEMPERATURE: 850°F. Min.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

May produce dense black smoke. Smoke consists of Carbon [soot] Carbon Monoxide Carbon Dioxide and Water. Dust generated by fabrication i.e., Sanding, Sawing, Etc. will increase fire hazard and should be handled accordingly.

V-REACTIVITY DATA

STABILITY [CONDITIONS TO AVOID]: Stable. Avoid Fire and High Temperatures.

INCOMPATIBILITY [MATERIALS TO AVOID]: Will dissolve in most organic solvents, and some insecticides, Aldehydes and Amines.

HAZARDOUS DECOMPOSITION: Carbon Monoxide Carbon Dioxide, Carbon, Water, Hydrogen Halide

HAZARDOUS POLYMERIZATION: None

MATERIAL SAFETY DATA SHEET

2 of 2

VI-HEALTH HAZARDS & FIRST AID

PRINCIPAL HEALTH HAZARDS & SIGNS & SYMPTOMS SKIN CONTACT: None

OF EXPOSURE:

INGESTION: Biologically inert. May act as an obstruction if swallowed.

EYE CONTACT: Dust or particles may cause mechanical eye irritation and/or injury.

CARCINOGENICITY: None

INHALATION: Dust from mechanical fabrication may cause upper respiratory irritation. Fumes from hot wire cutting can also cause upper respiratory irritation.

SAFETY PRECAUTIONS: Use positive ventilation. Mechanical Fabrication, Sanding, Etc. requires the use of safety glasses or goggles and dust mask.

FIRST AID

SKIN: Not expected to present skin hazard. wash exposed areas with mild soap and water. Consult physician if irritation persists.

EYES: Rinse with clean water. Remove foreign particles with clean, lint free cloth. Obtain medical attention if pain, blinking, tears or redness persist.

INGESTION: Not expected to present significant ingestion hazard. Consult physician if swallowed.

INHALATION: If overcome by exposure, remove to fresh air. Provide oxygen and artificial respiration. Get medical attention.

VII-EMPLOYEE PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Use approved safety glasses / goggles when sawing or sanding.

RESPIRATORY PROTECTION: Use approved dust mask when sawing or sanding.

GENERAL CONTROL MEASURES: Use positive ventilation. wear safety glasses / goggles and dust mask if mechanical fabrication is to take place.

SKIN PROTECTION: None required. Wear gloves and /or sleeves, if sensitivity noted.

VIII-ENVIRONMENTAL HAZARDS & PROTECTION

ENVIRONMENTAL HAZARDS: Sewer / Water Way Obstruction; fish may eat beads and obstruct their digestive tract.

REPORTABLE QUANTITY: None

SPILL, LEAK, OR RELEASE PROCEDURES: Normal good housekeeping should be observed.

DISPOSAL METHOD: Recycle, incinerate [WTE] or landfill per local and state regulations.

Material can be swept or picked up and placed into a suitable container for disposal.

IX-SPECIAL PRECAUTIONS

STORAGE AND HANDLING: Expanded Polystyrene, although it contains a fire retardant additive, is considered to be combustible and adequate protection from sources of ignition should be taken.

TRANSPORTATION REQUIREMENTS: Not a D.O.T. "HAZARDOUS MATERIAL"

ADDITIONAL INFORMATION

The information contained herein is provided for general reference purposes only. By providing the information contained herein, ARVRON, INC. makes no guaranty or warranty, and does not assume any liability, with respect to the accuracy or completeness of such information, or the product results in any specific instance, and hereby expressly disclaims any implied warranties of merchantability or fitness for a particular purpose, or any other warranties or representations whatsoever, expressed or implied.

ARVRON, INC.
STEER-O-CELL ®