

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** Perm-A-Barrier Liquid, Part A  
**MSDS Number:** M-85719  
**Cancelled MSDS Number:** M-85711  
**MSDS Date:** 01/13/2004  
**Chemical Family Name:** Fluid Applied Barrier made of Napthenic Oils and Inorganic filler.  
**Product Use:** Waterproofing  
**Chemical Formula:** Mixture-NA  
**CAS # (Chemical Abstracts Service Number):** Mixture-NA

**Manufactured by:**

W.R.Grace & Co.-Conn.  
62 Whittemore Avenue  
Cambridge, MA 02140

Grace Canada, Inc.  
294 Clements Road West  
Ajax, Ontario L1S 3C6

**In Case of Emergency Call:**

In USA: (617) 876-1400 In Canada: (905) 683-8561

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>CAS#</b>	<b>Percent (max)</b>
Calcium oxide	001305-78-8	25-50
Castor oil based ester	NJ801415063P	1-10
Chromium (III) oxide	001308-38-9	< 1
Distillates, petroleum, hydrotreated heavy naphthenic	064742-52-5	50-100
Quartz	014808-60-7	1-10
Titanium dioxide	013463-67-7	1-10
Zinc oxide	001314-13-2	1-10

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

---

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:**

**Caution!**

Causes eye irritation.

Causes skin irritation.

Causes digestive tract irritation if ingested.

Inhalation of vapor or spray causes irritation.

Product reacts with other component and also with water. Reaction is exothermic, releasing heat and fumes.

Mixed product contained in the pail may reach temperatures of 291°F.

Contact with hot material will cause burns.

Do not seal containers once mixed with other components or contaminated with water.

Sealed containers explode due to pressure from reaction.

**HMIS Rating:**

Health:	1
Flammability:	1
Reactivity:	1
Personal Protective Equipment:	B, G (See section 8)

**Potential Health Effects:**

**Inhalation:**

Not expected to be harmful. However, if mixed material is allowed to set in the container, temperatures up to 291°F can be reached liberating water vapor, carbon disulfide and other hydrocarbons. Inhalation of these materials can cause irritation.

Prolonged inhalation can cause lung damage.

Overexposure is not likely to occur unless specific use generates dust, vapors or mist.

Effects include: Flu-like symptoms (metal fume fever).

**Eye Contact:**

Eye contact causes irritation.

**Skin Contact:**

Skin contact causes irritation.

Contact with hot material will result in burns.

**Skin Absorption:**

Not expected to be harmful if absorbed through the skin.

**Ingestion:**

Due to the physical nature of this product, ingestion is not likely.

If ingested, causes irritation to the linings of the mouth, esophagus and stomach.

Effects include: Nausea, vomiting, sneezing, coughing, labored breathing and burns.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

---

**SECTION 4 - FIRST AID MEASURES:**

**Skin Contact:**

In case of skin contact, clean fingernails and wash skin with soap and water. If residue remains, clean with waterless handcream or abrasive soap. Never use solvents.  
If discomfort or irritation persists, consult a physician.  
Remove contaminated clothing and wash before reuse.

**Eye Contact:**

Flush eyes with water for at least 15 minutes while holding eyelids open.  
If discomfort or irritation persists, consult a physician.

**Ingestion:**

Do not induce vomiting.  
Never give anything by mouth to an unconscious person.  
If discomfort or irritation persists, consult a physician.

**Inhalation:**

If symptoms develop, get fresh air. If symptoms persist, consult a physician.  
If breathing has stopped, give artificial respiration then oxygen if needed.

---

**SECTION 5 - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point:</b>	Not Determined
<b>Flash Point Method:</b>	Not Applicable
<b>Lower Explosion Limit:</b>	Not Available
<b>Upper Explosion Limit:</b>	Not Available
<b>Auto-Ignition Temperature:</b>	Not Available

**NFPA Rating:**

<b>Health:</b>	1
<b>Flammability:</b>	1
<b>Reactivity:</b>	1

**Extinguishing Media:** In case of fire, use water spray, dry chemical, Carbon dioxide or foam.

**Special Fire Fighting Procedures:**

Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

**Unusual Fire and Explosion Hazards:**

None unless noted below.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
 MSDS ID Number: M-85719

MSDS Date: 01/13/2004

**SECTION 6 - ACCIDENTAL RELEASE MEASURES:**

**Spills/Leaks:**

Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

Oil spills released directly to waterways may be subject to National Response Center (1-800-424-8802) reporting. Immediately contact your company's environmental coordinator or the Grace Environmental Health and Safety Department.

**SECTION 7 - HANDLING AND STORAGE**

**Precautionary Measures:**

Use all product within 30-60 minutes of mixing to avoid an exothermic reaction (release of heat and fumes) Reaction times may vary depending upon temperature and mixing conditions.

Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Promptly cleanse hands after handling.

Use only with adequate ventilation.

Wear respiratory protection during spray applications.

Contact with hot material will result in burns.

Reaction releases heat and fumes if unused mixed product is allowed to sit in pail.

**FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.**

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

**EXPOSURE GUIDELINES (US)**

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Calcium oxide	2 mg/m3 TWA	-	-	5 mg/m3 TWA (not in effect as a result of reconsideration)	-	-	-
Castor oil based ester	-	-	-	-	-	-	-
Distillates, petroleum, hydrotreated heavy naphthenic	-	-	-	-	-	-	-
Quartz	0.05 mg/m3 TWA (respirable fraction)	-	-	0.1 mg/m3 TWA (respirable dust)	-	-	-
Titanium dioxide	10 mg/m3 TWA	-	-	10 mg/m3 TWA (total dust)	-	-	-
Zinc oxide	5 mg/m3 TWA (fume); 10 mg/m3 TWA (dust)	10 mg/m3 STEL (fume)	-	5 mg/m3 TWA (fume); 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 STEL (fume)	-	-

# W. R. GRACE

## MATERIAL SAFETY DATA SHEET

Product Name: Perm-A-Barrier Liquid, Part A

MSDS ID Number: M-85719

MSDS Date: 01/13/2004

---

### **EXPOSURE GUIDELINES (CANADA)**

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

**Engineering Controls:** Provide local exhaust ventilation to prevent vapor build up during application. This is particularly important in enclosed or confined areas where natural ventilation may not be adequate. Provide enough ventilation to maintain exposure levels below regulatory limits.

### **Personal Protective Equipment:**

**Respiratory Protection:** Respiratory protection may not be required in well ventilated areas. However, indoors or where ventilation is inadequate, the use of respirators equipped with organic vapor cartridges is required. During spray applications, the use of a dust/mist respirator such as a 3M Type P-95 with organic vapor (OV) protection (or equivalent) is required, but the specific respirator(s) may not adequately protect against actual working conditions which must be assessed periodically as work progresses. (See Work/Hygienic Practices.)

**Skin Protection:** Impervious (PVC, latex or nitrile) gloves should be worn any time direct contact is possible.

**Eye Protection:** At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

**Work/Hygienic Practices:** Use good personal hygiene practices.

Carbon disulfide and other potentially harmful gases, vapors and fumes may evolve as a result of exothermic reactions ("hot product") when components are mixed. Carbon disulfide may be detected by odor at about 1 ppm, but the ability to smell fatigues (diminishes) rapidly, therefore, odor does not serve as a good warning property. If eye or respiratory irritation occurs, or if a foul odor is detected, you may be experiencing exposure to Carbon disulfide and other organics. Leave the area immediately and seek fresh air.

Quartz (Crystalline silica) is a naturally-occurring mineral that is commonly contained in materials that are mined from the earth's surface such as sand, limestone, clay and gypsum (Calcium sulfate). Total quartz is a value usually representing the combined fractions of large, nonrespirable sized particles and of respirable sized particles (less than ten microns in aerodynamic diameter). It is only the respirable fraction of total quartz that is recognized as hazardous by professionals in the field of Occupational Health and by most regulatory agencies.

This product contains compounds subject to exposure guidelines and/or identified as carcinogens. (See Sections 8 and 11). However, due to the physical nature of this product, these compounds are unlikely to reach exposure limits unless airborne dust or spray mist is created.

# W. R. GRACE

## MATERIAL SAFETY DATA SHEET

Product Name: Perm-A-Barrier Liquid, Part A

MSDS ID Number: M-85719

MSDS Date: 01/13/2004

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
<b>Appearance/Odor:</b>	Greenish Semi-viscous Liquid
<b>Odor Threshold: (ppm)</b>	Not Determined
<b>pH:</b>	Not Available
<b>Vapor Pressure: (Mm Hg)</b>	Unknown
<b>Vapor Density: (Air = 1)</b>	Unknown
<b>Solubility In Water:</b>	Unknown
<b>Specific Gravity: (Water = 1)</b>	1.28
<b>Evaporation Rate: (Butyl Acetate = 1)</b>	Unknown
<b>Boiling Point:</b>	Not Determined
<b>Viscosity:</b>	Unknown
<b>Bulk Density: (Pounds/Cubic Foot)(Pcf)</b>	~83
<b>% Volatiles (gr/L): (70°F) (21°C)</b>	75 g/l

### SECTION 10 - STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable
<b>Conditions To Avoid:</b>	Heat, Strong acids, Organic materials, Water, phosphorous pentoxide, magnesium, rubber, linseed oil, hydrogen flouride, boric acid and the reaction process will cause a pressure build up in unvented containers and could result in an explosive release of pressure. Therefore, containers must not be sealed once the reaction has begun. Once the reaction is complete and the product is cured, this material is no longer sensitive to contact with water. .
<b>Hazardous Polymerization:</b>	Will not polymerize.
<b>Hazardous Decomposition Products:</b>	Carbon dioxide and toxic fumes of zinc oxide.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

---

**SECTION 11 - TOXICOLOGICAL INFORMATION**

**Ingredient(No data unless listed.)**      **CAS Number**      **LD50 and LC50**  
Zinc oxide                                      001314-13-2                                      Inhalation LC50 Mouse: 2500 mg/m<sup>3</sup>;  
Oral LD50 Mouse: 7950 mg/kg

**Carcinogenicity:**

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Calcium oxide	No	No	No	No	No	No
Castor oil based ester	No	No	No	No	No	No
Chromium (III) oxide	No	No	No	No	No	Yes
Distillates, petroleum, hydrotreated heavy naphthenic	No	No	No	No	No	No
Quartz	Yes	No	No	Yes	Yes	Yes
Titanium dioxide	No	No	No	No	No	No
Zinc oxide	No	No	No	No	No	No

Product contains less than 5% Quartz. Prolonged and repeated exposure to respirable Quartz (Crystalline silica) can decrease lung function and create risk of lung disease (i.e. silicosis and/or lung cancer). However, Quartz is not expected to be bio-available during routine use and application.

**Mutagenicity:**                                      Not applicable.  
**Teratogenicity:**                                      Not applicable.  
**Reproductive Toxicity:**                                      Not applicable.

---

**SECTION 12 - ECOLOGICAL INFORMATION**

**Environmental Fate:**                                      No data available for product.  
**Ecotoxicity:**    No data available for product.

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

**Waste Disposal Procedures:**

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

---

**SECTION 14 - TRANSPORTATION INFORMATION**

<b>Proper Shipping Name:</b>	Not Applicable
<b>UN/NA Number:</b>	Not Applicable
<b>Domestic Hazard Class:</b>	Nonhazardous
<b>Surface Freight Classification:</b>	Adhesive Cements N.O.I.
<b>Label/Placard Required:</b>	Not Applicable

---

**SECTION 15 - REGULATORY INFORMATION**

**REGULATORY CHEMICAL LISTS:**

**CERCLA (Comprehensive Response Compensation and Liability Act):**  
**(None present unless listed below)**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>CERCLA RQ</u></b>
-----------------------------	---------------------	--------------------	-------------------------

**SARA Title III (Superfund Amendments and Reauthorization Act)**

**SARA Section 312/Tier I & II Hazard Categories:**

Health Immediate (acute)	Yes
Health Delayed (chronic)	No
Flammable	No
Reactive	No
Pressure	No

**302 Reportable Ingredients (Identification Threshold 1%.):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>SARA 302 TPQ</u></b>
-----------------------------	---------------------	--------------------	----------------------------

**313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>
Zinc compounds	RR-00578-7	3.10831
Chromium Compounds	RR-00634-8	0.65

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part A  
MSDS ID Number: M-85719

MSDS Date: 01/13/2004

**National Volatile Organic Compound Emission Standards For Architectural Coatings:**

**Volatile Organic Content:** (gr/L) 75 g/l (as applied)

**WHMIS Classification(s):** D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

**State Regulatory Information:**

**California Proposition 65:** WARNING! This product contains substances known to the state of California to cause cancer, birth defects or other reproductive harm.

**Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Chromium (III) oxide	001308-38-9	.65
Quartz	014808-60-7	<5.0

**New Jersey Hazardous Substance List(Identification threshold (0.1%)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Chromium compounds	RR-00634-8	.65
Zinc compounds	RR-00578-7	3.10831

**Pennsylvania Hazardous Substance List(Identification threshold 0.01%):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

**CHEMICAL INVENTORY STATUS:**

**All chemicals in this product are listed or exempt from listing in the following countries:**

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	No	Yes	Yes	Yes	Not Determined	Yes	Not Determined

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

**SECTION 16 - OTHER INFORMATION**

**Non-Hazardous Ingredient Disclosure:**

**Chemical Name**

**CAS Number**

**Prepared by:** EH&S Department  
**Approved by:** EH&S Department  
**Approved Date:** 09/11/2003

**Disclaimer:**

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** Perm-A-Barrier Liquid, Part B  
**MSDS Number:** M-85722  
**Cancelled MSDS Number:** M-85712  
**MSDS Date:** 01/13/2004  
**Chemical Family Name:** Fluid applied made of Synthetic rubber latex.  
**Product Use:** Waterproofing  
**Chemical Formula:** Mixture-NA  
**CAS # (Chemical Abstracts Service Number):** Mixture-NA

**Manufactured by:**

W.R.Grace & Co.-Conn.  
62 Whittemore Avenue  
Cambridge, MA 02140

Grace Canada, Inc.  
294 Clements Road West  
Ajax, Ontario L1S 3C6

**In Case of Emergency Call:**

In USA: (617) 876-1400 In Canada: (905) 683-8561

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>CAS#</b>	<b>Percent (max)</b>
Styrene-Butadiene block copolymer	009003-55-8	50-100

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:**

**Caution!**

Causes eye irritation.

Causes skin irritation.

Product reacts with other component.

Reaction is exothermic, releasing heat and fumes.

Mixed product contained in pail may reach temperatures of 291°F.

Contact with hot material will result in burns.

Do not seal containers once mixed with other component.

Sealed container explode due to pressure from reaction.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

**HMIS Rating:**

Health:	1
Flammability:	0
Reactivity:	0
Personal Protective Equipment:	B, G (See Section 8)

**Potential Health Effects:**

**Inhalation:**

Not expected to be harmful. However, if mixed material is allowed to set in the container. Temperature up to 291°F can be reached, liberating water vapor, Carbon Disulfide and other Hydrocarbons. Inhalation of those materials can cause irritation. Prolonged inhalation can cause lung damage.

Effects include: Flu-like symptoms (metal fume fever).

**Eye Contact:**

Eye contact causes irritation.

**Skin Contact:**

Skin contact causes irritation.

**Skin Absorption:**

Not expected to be harmful if absorbed through the skin.

**Ingestion:**

Due to the physical nature of this product, ingestion of this product is not likely. If ingested, causes irritation to the linings of the mouth, esophagus and stomach. Effects include the following: Nausea, vomiting, sneezing, coughing, labored breathing and burns.

---

**SECTION 4 - FIRST AID MEASURES:**

**Skin Contact:**

In case of skin contact, clean fingernails and wash skin with soap and water. If residue remains, clean with waterless handcream or abrasive soap. Never use solvents.

If discomfort or irritation persists, consult a physician.

Remove contaminated clothing and wash before reuse.

**Eye Contact:**

Flush eyes with water for at least 15 minutes while holding eyelids open.

If discomfort or irritation persists, consult a physician.

**Ingestion:**

Do not induce vomiting.

Never give anything by mouth to an unconscious person.

If discomfort or irritation persists, consult a physician.

**Inhalation:**

If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

---

# W. R. GRACE

## MATERIAL SAFETY DATA SHEET

Product Name: Perm-A-Barrier Liquid, Part B

MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

### **SECTION 5 - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point:</b>	>300°F
<b>Flash Point Method:</b>	Estimated
<b>Lower Explosion Limit:</b>	Not Available
<b>Upper Explosion Limit:</b>	Not Available
<b>Auto-Ignition Temperature:</b>	Not Available

### **NFPA Rating:**

<b>Health:</b>	1
<b>Flammability:</b>	1
<b>Reactivity:</b>	0

**Extinguishing Media:** In case of fire, use water spray, dry chemical, Carbon dioxide or foam.

#### **Special Fire Fighting Procedures:**

Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion.

Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

#### **Unusual Fire and Explosion Hazards:**

None unless noted below.

---

### **SECTION 6 - ACCIDENTAL RELEASE MEASURES:**

#### **Spills/Leaks:**

Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

Oil spills released directly to waterways may be subject to National Response Center (1-800-424-8802) reporting. Immediately contact your company's environmental coordinator or the Grace Environmental Health and Safety Department.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

**SECTION 7 - HANDLING AND STORAGE**

**Precautionary Measures:**

Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

Wear respiratory protection during spray applications.

Reaction releases heat and fumes if unused mixed product is allowed to sit in pail. Contact with hot material will result in burns.

Use all product within 30-60 minutes of mixing to avoid an exothermic reaction (release of heat and fumes). Reaction times may vary depending upon temperature and mixing conditions.

Promptly cleanse hands after handling.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

---

**SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT**

**EXPOSURE GUIDELINES (US)**

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Styrene-Butadiene block copolymer	-	-	-	-	-	-	-

**EXPOSURE GUIDELINES (CANADA)**

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

**Engineering Controls:** Not generally required.

**Personal Protective Equipment:**

**Respiratory Protection:** Respiratory protection may not be required in well ventilated areas. However, indoors or where ventilation is inadequate, the use of respirators equipped with organic vapor cartridges is required. During spray applications, the use of a dust/mist respirator such as a 3M Type P-95 with organic vapor (OV) protection (or equivalent) is required, but the specific respirator(s) may not adequately protect against actual working conditions which must be assessed periodically as work progresses. (See Work/Hygienic Practices.)

**Skin Protection:** Impervious (PVC, latex or nitrile) gloves should be worn any time direct contact is possible.

**Eye Protection:** At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

# W. R. GRACE

## MATERIAL SAFETY DATA SHEET

Product Name: Perm-A-Barrier Liquid, Part B

MSDS ID Number: M-85722

MSDS Date: 01/13/2004

**Work/Hygienic Practices:** Use good personal hygiene practices.

Carbon disulfide and other potentially harmful gases, vapors and fumes may evolve as a result of exothermic reactions ("hot product") when components are mixed. Carbon disulfide may be detected by odor at about 1 ppm, but the ability to smell fatigues (diminishes) rapidly, therefore, odor does not serve as a good warning property. If eye or respiratory irritation occurs, or if a foul odor is detected, you may be experiencing exposure to Carbon disulfide and other organics. Leave the area immediately and seek fresh air.

### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
<b>Appearance/Odor:</b>	A milky white aqueous dispersion with mild aromatic odor.
<b>Odor Threshold:</b> (ppm)	Not Determined
<b>pH:</b>	9-12
<b>Vapor Pressure:</b> (Mm Hg)	Unknown
<b>Vapor Density:</b> (Air = 1)	Unknown
<b>Solubility In Water:</b>	Miscible
<b>Specific Gravity:</b> (Water = 1)	1.0
<b>Evaporation Rate:</b> (Butyl Acetate = 1)	Unknown
<b>Boiling Point:</b>	>212°F/100°C
<b>Viscosity:</b>	Unknown
<b>Bulk Density:</b> (Pounds/Cubic Foot)(Pcf)	~60
<b>% Volatiles (gr/L):</b> (70°F) (21°C)	Not Available

### SECTION 10 - STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable
<b>Conditions To Avoid:</b>	Strong oxidizers.
<b>Hazardous Polymerization:</b>	Will not polymerize.
<b>Hazardous Decomposition Products:</b>	Carbon dioxide and Carbon monoxide.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

**SECTION 11 - TOXICOLOGICAL INFORMATION**

**Ingredient(No data unless listed.)**                      **CAS Number**                      **LD50 and LC50**

**Carcinogenicity:**

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Styrene-Butadiene block copolymer	No	No	No	No	No	No

**Mutagenicity:**    Not applicable.  
**Teratogenicity:**    Not applicable.  
**Reproductive Toxicity:**    Not applicable.

---

**SECTION 12 - ECOLOGICAL INFORMATION**

**Environmental Fate:**    No data available for product.  
**Ecotoxicity:**    No data available for product.

---

**SECTION 13 - DISPOSAL CONSIDERATIONS**

**Waste Disposal Procedures:**  
Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

---

**SECTION 14 - TRANSPORTATION INFORMATION**

**Proper Shipping Name:**    Not Applicable  
**UN/NA Number:**    Not Applicable  
**Domestic Hazard Class:**    Nonhazardous  
**Surface Freight Classification:**    Adhesive Cement N.O.I.  
**Label/Placard Required:**    Not Applicable

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---

**SECTION 15 - REGULATORY INFORMATION**

---

**REGULATORY CHEMICAL LISTS:**

**CERCLA (Comprehensive Response Compensation and Liability Act):**  
**(None present unless listed below)**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>CERCLA RQ</u></b>
-----------------------------	---------------------	--------------------	-------------------------

**SARA Title III (Superfund Amendments and Reauthorization Act)**

**SARA Section 312/Tier I & II Hazard Categories:**

Health Immediate (acute)	No
Health Delayed (chronic)	No
Flammable	No
Reactive	No
Pressure	No

**302 Reportable Ingredients (Identification Threshold 1%.):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>	<b><u>SARA 302 TPQ</u></b>
-----------------------------	---------------------	--------------------	----------------------------

**313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):**

<b><u>Chemical Name</u></b>	<b><u>CAS #</u></b>	<b><u>Wt %</u></b>
1,3-Butadiene	000106-99-0	.005
Styrene	000100-42-5	.02

**National Volatile Organic Compound Emission Standards For Architectural Coatings:**

**Volatile Organic Content:** 75 g/l (as applied)

**WHMIS Classification(s):** D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

**State Regulatory Information:**

**California Proposition 65:** WARNING! This product contains substances known to the state of California to cause cancer, birth defects or other reproductive harm.

**Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
1,3-Butadiene	000106-99-0	.005
Styrene	000100-42-5	.02

**New Jersey Hazardous Substance List(Identification threshold (0.1%)):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

**Pennsylvania Hazardous Substance List(Identification threshold 0.01%):**

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

**CHEMICAL INVENTORY STATUS:**

All chemicals in this product are listed or exempt from listing in the following countries:

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	Yes	No	Yes	Yes	Yes	Yes	Yes

**SECTION 16 - OTHER INFORMATION**

**Non-Hazardous Ingredient Disclosure:**

<u>Chemical Name</u>	<u>CAS Number</u>
Water	007732-18-5

**Prepared by:** EH&S Department  
**Approved by:** EH&S Department  
**Approved Date:** 01/13/2004

**Disclaimer:**

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."

**W. R. GRACE**  
**MATERIAL SAFETY DATA SHEET**

Product Name: Perm-A-Barrier Liquid, Part B  
MSDS ID Number: M-85722

MSDS Date: 01/13/2004

---