



Material Safety Data Sheet

Preparation Date: 04-Jan-2010

Revision Date: 29-Dec-2009

Revision Number: 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code C660-NOPG
Trade Name PRIME A PELL 200
Contact Manufacturer Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372
Emergency Telephone Number 800-535-5053 (INFOTRAC) - TNE MEC REGULATORY DEPT: 816-474-3400

2. HAZARDS IDENTIFICATION

Emergency Overview

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
HARMFUL OR FATAL IF SWALLOWED.
MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA.
MAY CAUSE EYE, SKIN, NOSE, THROAT AND RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Principle Routes of Exposure Eye contact, Inhalation, Skin contact.

Acute Effects

Eyes May cause slight irritation.
Skin Irritating to skin.
Inhalation Irritating to respiratory system.
Ingestion May be harmful if swallowed.

Chronic Effects

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system. Kidney disorders. Skin disorders.

Interactions with Other Chemicals Use of alcoholic beverages may enhance toxic effects.

Potential Environmental Effects See Section 12 for additional Ecological information

Target Organ Effects Central nervous system, Eyes, Kidney, Respiratory system, Skin

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Component	CAS-No	Weight %
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	92.4182

3. COMPOSITION/INFORMATION ON INGREDIENTS

SILICONE RESIN SOLUTION		5 - 10
-------------------------	--	--------

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Combustible material.
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Contact with water may cause violent frothing. Use: Carbon dioxide (CO ₂) - Foam - Dry chemical
Hazardous Decomposition Products	Oxides of carbon, hydrocarbons.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapours. In the event of fire and/or explosion do not breathe fumes.

Protective Equipment and Precautions for Firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. May cause heat and pressure build-up in closed containers. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Cleaning Up	If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.
Other Information	Not applicable

7. HANDLING AND STORAGE

Handling

Close container after each use. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Storage

Keep away from heat, sparks and flame. Use only in an area containing flame proof equipment. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	Quebec TWAEV	Ontario TWAEV	Mexico OEL (TWA)
ALIPHATIC HYDROCARBON MIXTURE	TWA: 100 ppm	TWA: 100 ppm TWA: 525 mg/m ³ TWA: 2900 mg/m ³ TWA: 500 ppm	TWA: 525 mg/m ³ TWA: 100 ppm	TWA: 525 mg/m ³	TWA: 523 mg/m ³ TWA: 100 ppm STEL: 1050 mg/m ³ STEL: 200 ppm

Engineering Measures

Ensure adequate ventilation, especially in confined areas

Personal Protective Equipment

Skin Protection

Lightweight protective clothing, Apron, Impervious gloves

Eye/face Protection

Safety glasses with side-shields

Respiratory Protection

Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	39°C / 102.0°F
Method	Pensky Martens - Closed Cup
Boiling Point/Range	154 - 202°C / 310.0 - 395.0°F
Upper Exposure Limits	No information available
Lower Exposure Limits	No information available
Evaporation Rate	No information available
Vapour Pressure	No information available
Vapour Density	No information available
Specific Gravity	.77954
Density	6.48694
VOC Content (lbs/gal)	6.067
% Volatile by Weight	93.5180
% Volatile by Volume	95.5065

10. STABILITY AND REACTIVITY

Chemical stability	Stable.	Conditions to Avoid	Heat, flames and sparks.
Incompatible Products	Strong oxidizing agents. Acids.	Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

Irritation	No information available
Corrosivity	No information available
Sensitization	No information available

11. TOXICOLOGICAL INFORMATION

Chronic Toxicity

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen

Mutagenic Effects	No information available
Reproductive Effects	No information available
Developmental Effects	No information available
Teratogenicity	No information available
Target Organ Effects	Central nervous system, Eyes, Kidney, Respiratory system, Skin.
Endocrine Disruptor Information	No information available

12. ECOLOGICAL INFORMATION

Ecotoxicity

.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated Packaging Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT Ground Transportation Only. Call TNEMEC Traffic Department - 816-474-3400 for other modes of Transportation.
Proper Shipping Name UN1263, PAINT RELATED MATERIAL, 3, PGIII, ERG 128

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not Comply
CHINA	Does not Comply
ENCS	Does not Comply
KECL	Does not Comply
PICCS	Does not Comply
AICS	Does not Comply

U.S. Federal Regulations

SARA 313

SARA 311/312 Hazardous Categorization

Chronic Health Hazard	No
Acute Health Hazard	Yes
Fire Hazard	Yes

Sudden Release of Pressure Hazard
 Reactive Hazard

No
 No

CERCLA

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ALIPHATIC HYDROCARBON MIXTURE	X	X	X		X

Other International Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B3 Combustible liquid

D2B Toxic materials



Component	NPRI
ALIPHATIC HYDROCARBON MIXTURE	Part 5 Substance

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Revision Date: 29-Dec-2009

Revision Summary: No information available

HMIS Health 2 Flammability 2 Reactivity 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy of completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS