

# Glass Block - VISTABRIK®

Solid Glass Block - High Performance Line



PITTSBURGH CORNING™

## Product Description

Three inches of solid glass block. Clear visibility, durable, impact, vandal and bullet resistant. Low maintenance and aesthetically attractive. Excellent light transmission.

Nominal Size (Actual size is 1/4" less than nominal; mm shown is actual)	Weight (lb/ft²) installed with mortar	Heat Transmission U Value (Btu/hr ft² °F)	Thermal Resistance R Value (hr ft² °F/Btu)	Visible Light Transmission (%)	Shading Coef.	Sound Transmission S.T.C.	Solar Heat Gain Coefficient
8" x 8" x 3" Nominal 7-5/8" x 7-5/8" x 3" Actual (194mm x 194mm x 76mm)	40	0.87	1.15	80	-	53 (NRC=0.05)	.75-.78
3" x 8" x 3" Nominal 3" x 7-5/8" x 3" Actual (76mm x 194mm x 76mm)	40	0.87	1.15	80	-	-	.75-.78
4" x 8" x 3" Nominal 3-5/8" x 7-5/8" x 3" Actual (92mm x 194mm x 76mm)	40	0.87	1.15	80	-	-	.75-.78

**For technical assistance call us toll free at 1-800-659-4731.**