

Glass Block - Vue®

THICKSET® - High Performance Line



PITTSBURGH CORNING™

Product Description

The thicker-faced blocks offer an extra reduction in sound transmission and increased fire resistance available in 60 or 90-minute ratings. The Vue® pattern transmits maximum light and allows ultimate visibility.

- THICKSET® 60 Block Vue® Pattern provides 60-minute fire rating.
- THICKSET® 90 Block Vue® Pattern provides 90-minute fire rating.

Nominal Size (Actual size is 1/4" less than nominal; mm shown is actual)	Weight (lb/ft²) installed with mortar	Heat Transmission U Value (Btu/hr ft² °F)	Thermal Resistance R Value (hr ft² °F/Btu)	Visible Light Transmission (%)	Shading Coef.	Sound Transmission S.T.C.	Solar Heat Gain Coefficient
THICKSET® Block – Nominal Thickness = 4"; Actual Thickness = 3-7/8" (98mm)							
THICKSET® 60 Block Vue® Pattern							
8" x 8" (197mm)	25	0.51	1.96	75	0.65	48	.66-.68
THICKSET® 90 Block Vue® Pattern							
8" x 8" (197mm)	30	0.51	1.96	70	0.65	50	.66-.68

For technical assistance call us toll free at 1-800-659-4731.