

Everlastic Neoprene Cord

Material: Closed Cell Neoprene Sponge Rubber
Specification: ASTM D 1056 2C1 or ASTM C-509
Diameters Available: 1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 1", 1-1/4"*, 1-3/4"*, 2"*, 2-3/8", 2-3/4"
*Standard Sizes with inside Diameters other sizes by Special Order.

Standard CCPE Backer Rod

Material: Closed Cell Polyethylene Foam
Specification: TT-S-00227E
Diameters Available: 1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1-1/4", 1-1/2", 1-3/4", 2", 2-1/2", 3", 4"
Diameters 1-1/4" or less packaged in coils, larger sizes in six foot pieces.

Hot Rod XL

Material: Crosslinked Closed Cell Polyethylene Foam
Specification: ASTM D 1622
Diameters Available: 3/8", 1/2", 5/8", 3/4", 1", 1-1/4", 1-1/2", 1-3/4", 2"
Diameters 1-1/4" or less packaged in coils, larger sizes in six foot pieces.

Soft Type Backer Rod

Material: Extra Soft & pliable, Closed Cell Polyethylene Foam
Specification: ASTM D 249-92 Type 3
Diameters Available: 3/8", 5/8", 7/8", 1-1/8", 1-1/2", 2"
Diameters 1-1/4" or less packaged in coils, larger sizes in six foot pieces.

Tundra Foam

Material: Open Cell Polyethylene Foam
Specification: ASTM D 1564
Diameters Available: 3/8", 5/8", 7/8", 1", 1-1/8", 1-1/2", 2"
Furnished in twice compressed six pack bundles.

MASONPRO, Inc.
43300 Seven Mile Road
Northville, MI 48167
1-800-659-4731



We do not guarantee the applicability or accuracy of this information or the suitability of our products for any given situation. Users should make their own tests to determine the suitability of any product for their particular purpose. The products discussed are sold without warranty, either expressed or implied, buyer assumes all responsibility for any loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.