

Commercial & Residential Cavity Wall Construction

Use: Used in traditional masonry, steel and wood stud cavity wall construction.

Mason ProNet™ is placed directly on top of flashing at base of wall, above doors, windows and other openings and flashed areas.

Mason ProNet™ is a 90% open weave mesh design and will not oxidize, rot, promote mold or fungus, or react with other common building materials.

Recycled polyester material; 17% post-consumer and 33% pre-consumer.



Install: After laying one or two courses of brick, place a continuous row of Mason ProNet™ in cavity or collar joint on flashing against inside of outer wythe. For wall-cavities that exceed 9' in height, place an additional continuous strip on wall reinforcing anchors/ties at every 9' of wall height.

Sizes: 0.4", 1" & 2" strips
10" (H) x 5' (L)

Quantity: 0.4": 250 L.F. per box
1" & 2": 100 L.F. per box

Weep Vents: Include Weep Vents for a complete drainage system.
Available in 6 colors: Brown, tan, red, almond, white or gray

Benefits: Cost-effective and easy to install.
Requires no fasteners or adhesives, no special skills or tools.
Compressible to allow for variation in wall cavities.



Technical Assistance: For technical assistance please call the Mason Pro offices at 1-800-659-4731 or visit our website at www.masonpro.com