

TABLE 2A
UNREINFORCED INTERNALLY BRACED ALLOWABLE WALL HEIGHTS
(INTERMEDIATE PERIOD)

CMU Wall Thickness & Grouting	Type S Mortar Cement Or Portland Cement/Lime	Type S Masonry Cement Or Air Entrained Portland Cement/Lime
8" UngROUTed	10'-0"	8'-0"
12" UngROUTed	14'-8"	12'-0"
8" Solid Grouted	18'-0"	18'-0"
12" Solid Grouted	29'-4"	28'-0"

Notes

- 1) Table heights also applicable with Type M mortar.
- 2) Table valid for masonry densities of 95 pcf and heavier.

Produced for educational purposes only.

By: Todd Dailey, PE

Dailey Engineering, Inc.

www.daileyengineeringinc.com

todddailey@me.com

DISCLAIMER: The decision to utilize this information is not within the purview of Dailey Engineering, Inc. and persons making use of this information do so at their own risk. Dailey Engineering, Inc. makes no representation or warranties, expressed or implied, with respect to the accuracy or suitability of this information. Dailey Engineering, Inc. disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, which may result from the use of this information. This information is not to be interpreted as indicating compliance with, or waiver of, any provision of any applicable building code, ordinance, standard or law.

DISCLAIMER: This table is intended for use by those persons who are qualified and competent to evaluate the significant and limitations of its content. Dailey Engineering, Inc. disclaims any and all responsibility for the application of the stated material.