



TECHNICAL DATA SHEET

WINDOW, DOOR & SIDING

H2U

HIGH PERFORMANCE

Description: OSI H2U Window, Door, Siding and Trim Sealant is a high performance sealant designed for the siding and window industries. This superior acrylic urethane formula has better adhesion, flexibility and durability than most sealants, and cleans up easily with soap and water. This water based, low gassing formula is ideal for use indoors and provides the durability, flexibility and adhesive strength needed for outdoor use. OSI H2U dries to a glossy sheen and when fully cured it is paintable and will resist surface mold and mildew.

Available As:

Item #	Size	Color
1256934	10 fl oz (295 ml)	White
1584644	10 fl oz (295 ml)	Brown
1256935	10 fl oz (295 ml)	Clay
1283154	10 fl oz (295 ml)	Beige
1283158	10 fl oz (295 ml)	Almond
1256965	10 fl oz (295 ml)	Clear

Features & Benefits:

- Superior Durability
- Permanently Flexible
- Indoor / Outdoor Capabilities
- Easy Water Clean-Up

Recommended For:

Developed primarily for sealing around exterior window and door frames, sill plates, electrical and plumbing penetrations and other areas where water and air can infiltrate. This product is ideal for sealing gaps and cracks found on the interior of the home. Works well along baseboards, floors, wall to floor joints, around window and door frames, ceiling to wall joints and any other crack or gaps found in and around the home. Works well on vinyl, aluminum and fiber cement siding, brick, concrete, metal, all types of wood, drywall, plaster, plastic moldings, tile and most common building materials.

For Best Results:

Not recommended for the following applications:

- Underwater applications or permanent water immersion
- Applications requiring temperature resistance greater than 170°F (77°C)
- Exterior use when rain or freezing conditions are expected within 24 hours
- Butt joint applications
- Application on unfinished or unprimed fiber cement (Fiber cement must be primed or have a factory finish before application)
- Application on mirrors

Coverage:

For a 10 fl. oz. (295 mL) cartridge:

- A 1/4" (6 mm) bead extrudes approximately 31 ft. (9.5 m)
- A 3/8" (9.5 mm) bead extrudes approximately 14 ft. (4.2 m)



TECHNICAL DATA SHEET

Typical Uncured Physical Properties:

Color:	Various	Note: Clear extrudes white but turns clear as it dries
Appearance:	Non-slumping paste	
Base:	Acrylic/Urethane Latex	
Odor:	Mild acrylic odor	
Specific Gravity:	1.267	
Viscosity:	200,000 to 300,000 cps	
% Solids by Weight:	70%	
VOC Content:	0.3% by weight	CARB
	42 g/l	SCAQMD rule 1168
Shelf Life:	24 months from date of manufacture (unopened)	
Lot Code Explanation:	YYDDD	
Stamped on body side of cartridge near plunger	YY = Last two digits of year of manufacture	
	DDD = Day of manufacture based on 365 days in a year	
	For example: 14061 = 61 st day of 2014 = March 2, 2014	

Typical Application Properties:

Application Temperature:	Above 40°F (5°C)	
Tooling / Open Time:	5-10 minutes*	At 73°F and 50% relative humidity
Tack-Free Time:	30-60 minutes*	
Cure Time:	1-14 days*	
	*Time is dependent on temperature, humidity, porosity of substrate and depth of sealant applied	
Extrusion Force:	5/16" opening at 5 in/min	
At 73°F:	35 lbs	
At 41°F:	56 lbs	
Sag or Slump:	0.1 inches maximum	ASTM D2202, at 120°F

Typical Cured Performance Properties:

Color:	Various	
Cured Form:	Non-flammable solid	
Service Temperature:	-5°F (-21°C) to 170°F (77°C)	
Paintable:	Yes, once fully cured	
Shrinkage:	Approx. 30%	
Hardness:	24 ± 1	Shore A
Elongation at Break:	ASTM D412 Die C	
Initial - 5 day cure at 73°F:	1106 ± 317%	
Full Cure – 30 days at 122°F:	468 ± 38%	
Tensile Strength at Break:	ASTM D412 Die C	
Initial - 5 day cure at 73°F:	72 ± 33 psi	
Full Cure – 30 days at 122°F:	302 ± 5 psi	
% Recovery:	ASTM D412 Die C	
Initial - 5 day cure at 73°F:	42 ± 6%	
Full Cure – 30 days at 122°F:	83%	
Joint Movement Capability:	± 25%	After 14 days
180° Peel Adhesion:	ASTM D794	
Vinyl Siding	19 ± 2.1 pli	
Aluminum Flashing (coated)	18.6 ± 5.5 pli	
Fiber cement - Primed	6.2 ± 2.1 pli	
Pine	9.3 ± 2.7 pli	



TECHNICAL DATA SHEET

OSB (glossy side)	9.6 ± 1.1 pli
PVC Trim	5.3 ± 0.7 pli
Specifications:	Meets the performance requirements of the following: <ul style="list-style-type: none">• ASTM C920 Type S, Grade NS, Class 25• Fed. Spec TT-00230C Type II, Class A• GreenGuard® Certified• Qualifies for LEED® points

Directions:

Tools Typically Required:

Utility knife, caulking gun and tool to puncture cartridge seal. For best application results, OSI® recommends the use of a high quality caulking gun such as the Albion® B12 Cartridge Gun.

Safety Precautions:

Wear gloves and wash hands after use.

Preparation:

The temperature of the product, the surfaces and the working area must be above 41°F (5°C). For best performance, apply sealant at 70°F (21°C). Ensure surfaces to be sealed are clean, dry, structurally sound and free of dust, grease, oil, and other foreign contaminants. Concrete or block walls must be well cured, dry and free of any release agents. Cut off tip of cartridge at a 45° angle to desired bead size (3/8" recommended).

Application:

Maximum joint size should not exceed 5/8" (15.9 mm) x 1/2" (12.7 mm). Using caulking gun, force sealant into joint. Avoid outdoor use when rain is expected within 24 hours. Tool if necessary with a wet finger within 5 minutes after application. Sealant skins over in approximately 30 minutes depending on humidity and temperature. Note: Clear H2U extrudes white and will turn clear as it dries.

Clean-up:

Clean tools and uncured product residue immediately with warm, soapy water. Cured sealant may be carefully cut away with a sharp-edged tool.

Storage & Disposal:

DAMAGED BY FREEZING. Store in a cool, dry location at room temperature. For maximum shelf life store at 75°F (24°C). Take unwanted product to an approved household hazardous waste transfer facility. Hardened material may be disposed of as non-hazardous trash.

Label Precautions:

CAUTION! MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.

CAUTION! Contains ethylene glycol and mineral oil. Avoid contact with eyes and skin. Use with adequate ventilation. Do not swallow. **FIRST AID:** If swallowed do not induce vomiting, call a physician or Poison Control center. For eye contact flush with water for 15 minutes. For skin contact, wash with soap and water. If affected by inhalation, get fresh air. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Refer to the Safety Data Sheet (SDS) for further information.

Limited Warranty:

This product is warranted to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This limited warranty gives you specific legal rights, which vary from state to state. Henkel may be contacted at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET for warranty assistance.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



TECHNICAL DATA SHEET



OSI Tougher than the Elements. For Professional Use Only. The Battle will be Fierce.

OSI works side by side with residential builders, contractors and remodeling professionals who use our products everyday on their jobsites. OSI combines this deep understanding with the sophisticated global innovation and manufacturing excellence of Henkel to make the world's best professional-grade caulks, sealants and adhesives.

1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET

www.ositough.com



OSI Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067

www.henkelna.com

Revision Date: 07/31/2014 Supercedes: 05/01/2012 Ref. #: WDM230 Post Date: 07/31/2014