



**LEED® NEW CONSTRUCTION (NC) RATING SYSTEM INFORMATION**  
**Loctite® PL® 300 Foamboard Construction Adhesive**  
**IDHs 1421941, 1421930**

May 25, 2015

Loctite® PL® 300 Foamboard Construction Adhesive qualifies for the following points under the LEED® for New Construction Rating System v2.2:

**Indoor Environmental Quality (EQ):**

**EQc4.1 | Low-Emitting Materials: Adhesives & Sealants | 1 point**

Requirements:

The VOC Content of Drywall and Panel Adhesives must be less than 50 g/L.

Loctite® PL® 300 Foamboard Construction Adhesive qualifies for this credit as the VOC Content is 33g/L.

**Materials & Resources (MR):**

**MRc4.1 | Recycled Content: 10% | 1 point**

**MRc4.2 | Recycled Content: 20% | 1 additional point**

Requirements:

Use materials with recycled content equal to at least 10% (or 20%) of the total value of the materials in the project.

Loctite® PL® 300 Foamboard Construction Adhesive does not qualify for this credit as it contains:

- 0% post-consumer recycled content
- 0% pre-consumer recycled content

**MRc5.1 | Regional Materials: 10% Extracted, Processed & Manufactured | 1 point**

**MRc5.2 | Regional Materials: 20% Extracted, Processed & Manufactured | 1 additional point**

Requirements:

Use building materials or products that have been manufactured within 500 miles of the project site.

Loctite® PL® 300 Foamboard Construction Adhesive is manufactured and packaged at Henkel Corporation, 1600 Executive Drive, Lagrange, GA, USA\*.

\* The raw materials are obtained from different sources and the extraction and processing sites may vary. For this reason, the extraction and processing sites of the materials used to manufacture this product are not determined.