



Safety Data Sheet

Issue Date 26-Jun-2015

Revision Date 26-Jun-2015

Revision Number 6

1. IDENTIFICATION

Product identifier

Product Code C660-NOPG
Product Name PRIME A PELL 200 CLEAR

Other means of identification

Common Name SERIES 660

Recommended use of the chemical and restrictions on use

Recommended Use industrial paint.
Uses advised against Consumer use, For professional use only. Not for residential use.

Details of the supplier of the safety data sheet

Manufacturer Address

Tnemec Company, Inc. 6800 Corporate Drive, Kansas City, MO 64120-1372

Emergency telephone number

Company Phone Number Tnemec Regulatory Dept: 816-474-3400
24 Hour Emergency Phone Number 800-535-5053 (Infotrac)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable Liquids	Category 3

Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause genetic defects
May cause cancer
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Flammable liquid and vapor

**Appearance** clear**Physical state** liquid**Odor** Strong aromatic**Precautionary Statements****Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/mixing/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge

Response

IF exposed or concerned: Get medical advice/attention
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting
 In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep cool
 Keep away from children

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

May cause skin and eye irritation

Other information

May be harmful in contact with skin

SEE SAFETY DATA SHEET

Acute Toxicity

0 % of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No	Weight-%
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	60 - 100%
SILICONE RESIN SOLUTION	-	1 - 10%
METHYL ALCOHOL	-	0 - 0.1%

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Inhalation	Remove to fresh air. Oxygen or artificial respiration if needed.
Ingestion	If swallowed, do not induce vomiting. Get medical attention immediately.
Self-protection of the first aider	Use personal protective equipment. Avoid contact with eyes, skin and clothing.

Most important symptoms and effects, both acute and delayed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Foam. Dry powder. Carbon dioxide. alcohol-resistant foam.

Unsuitable extinguishing media Water spray.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours In the event of fire and/or explosion do not breathe fumes

Hazardous combustion products Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

Protective equipment and precautions for firefighters

Use water spray to cool unopened containers. In the event of fire, wear self-contained breathing apparatus. Keep away from heat/sparks/open flames/hot surfaces. MAY CAUSE HEAT AND PRESSURE BUILD-UP IN CLOSED CONTAINERS. Solvent vapors are heavier than air and may spread along floors. Flash back possible over considerable distance.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Avoid contact with eyes, skin and clothing. Use personal protective equipment. Remove all sources of ignition.

Environmental Precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

Methods for cleaning up If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Close container after each use. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when using this product. If splashes are likely to occur, wear goggles. Wear protective gloves/clothing. Do not burn, or use a cutting torch on, the empty drum. When used in a mixture, read the labels and safety data sheets of all components. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible products Water. Bases. Acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	TWA: 100 ppm	TWA: 100 ppm TWA: 525 mg/m ³ TWA: 500 ppm TWA: 2900 mg/m ³	20000 mg/m ³
METHYL ALCOHOL	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³ Skin	6000 ppm

Appropriate engineering controls

Engineering measures Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses with side-shields If splashes are likely to occur, wear face-shield.

Skin and body protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only with adequate ventilation. Do not breathe vapors, spray mist, or dust. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist or dust levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Avoid breathing dust created by cutting, sanding, or grinding.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Strong aromatic
Appearance	clear	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH		No data available
Melting point / freezing point		No data available
Boiling point / boiling range	154 °C / 310.0 °F	
Flash point	38 °C / 100.0 °F	Pensky Martens - Closed Cup
Evaporation rate		No data available
Flammability (solid, gas)		Not applicable
Flammability Limit in Air		No data available
Upper flammability limit	N/A	
Lower flammability limit	N/A	
Vapor pressure		No data available
Vapor density		No data available
Specific gravity	.77954	g/cm3
Water solubility	Insoluble in cold water	
Solubility in other solvents		No data available
Partition coefficient: n-octanol/water		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity		No data available

Other Information

Density	6.48693 lbs/gal
Volatile organic compounds (VOC) content	6.070 lbs/gal
Total volatiles weight percent	93.5760 %
Total volatiles volume percent	95.5606 %

10. STABILITY AND REACTIVITY**Reactivity**

Water reactive

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible materials

Water, Bases, Acids, Strong oxidizing agents

Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Carbon dioxide. Hydrocarbons. Formaldehyde.

11. TOXICOLOGICAL INFORMATION**Information on Likely Routes of Exposure**

Inhalation	May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye contact	May cause temporary eye irritation.
Skin contact	Prolonged contact may cause redness and irritation.
Ingestion	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
METHYL ALCOHOL	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin disorders.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Sensitization No information available.

Mutagenicity May cause genetic defects.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH	IARC	NTP	OSHA
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3				

Reproductive effects No information available.

STOT - single exposure No information available

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure

Target organ effects Central nervous system, kidney, respiratory system, Skin.

Aspiration hazard Risk of serious damage to the lungs (by aspiration).

Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

92.4184 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Toxicity to algae	Toxicity to fish	Toxicity to daphnia
METHYL ALCOHOL		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

Component	log Pow
METHYL ALCOHOL	-0.77

Other Adverse Effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods Keep container tightly closed. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ALCOHOL		Included in waste stream: F039		U154

Component	CAWAST
METHYL ALCOHOL	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name paint in oil

IATA

UN/ID no. 1263

Hazard Class 3

Packing Group III

EmS No. 366

Additional information Call TNE MEC Traffic Department - 816-474-3400 for additional information or other modes of Transportation.

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

Component HAPS Data
METHYL ALCOHOL

United States of America

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40n of the Code of Federal Regulations, Part 372.

Component	SARA 313 - Threshold Values
METHYL ALCOHOL -	1.0

SARA 311/312 Hazardous

Categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs	RQ
METHYL ALCOHOL	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

United States of America

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer

Component	California Prop. 65
ALIPHATIC HYDROCARBON MIXTURE - 8052-41-3	.
METHYL ALCOHOL -	Developmental

California SCAQMD Rule 443

Contains Photochemically Reactive Solvent

State Right-to-Know

Component	New Jersey	Massachusetts	Pennsylvania
ALIPHATIC HYDROCARBON MIXTURE 8052-41-3	X	X	X
METHYL ALCOHOL	X	X	X

16. OTHER INFORMATION

NFPA Health 2 Flammability 2 Instability 1 Physical hazard *
HMIS (Hazardous Material Information System) Health 2* Flammability 2 Reactivity 1

Prepared By Tnemec Regulatory Dept: 816-474-3400
 Revision Date 26-Jun-2015
 Revision Summary
 9 4 5 7 8 10 11 14 15 1

Disclaimer

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.

To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

End of MSDS