



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

**Product name: STYROFOAM™ CAVITYMATE™ 3.00 X 16
Inch Butt Edge Cavity Wall Extruded Foam Insulation**

Issue Date: 07/30/2018

Print Date: 07/31/2018

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

**Product name: STYROFOAM™ CAVITYMATE™ 3.00 X 16 Inch Butt Edge Cavity Wall Extruded
Foam Insulation**

Recommended use of the chemical and restrictions on use

Identified uses: Thermal insulation.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2030 DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200
Combustible dust

Label elements

Signal word: **WARNING!**

Hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Construction and composite applications

This product is an article.

Component	CASRN	Concentration
2-Propenenitrile, polymer with ethenylbenzene	9003-54-7	> 60.0 - < 100.0 %
Styrene, polymers	9003-53-6	<= 10.0 %
1,1,1,2-Tetrafluoroethane	811-97-2	>= 5.0 - <= 10.0 %

Note

Extruded polystyrene foam containing a halogenated flame retardant system.

4. FIRST AID MEASURES

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Combustion products may include and are not limited to: Hydrogen halides. Based on combustion toxicity testing, the effects of combustion from this foam are not more acutely toxic than the effects of combustion from common building materials such as wood.

Unusual Fire and Explosion Hazards: Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product contains a flame retardant to inhibit accidental ignition from small fire sources. This plastic foam product is combustible and should be protected from flames and other high heat sources. For more information, contact Dow. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct waterstream. Use fine water spray or foam. Cool surroundings with water to localize fire zone.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Use ventilation adequate to keep exposures below recommended exposure limits. See the safety datasheet. Do not enter confined spaces unless adequately ventilated. Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product is combustible and

may constitute a fire hazard if improperly used or installed. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: When large quantities of this product are stored or fabricated, blowing agents may be released. Released blowing agents may thermally decompose to form gases which may accelerate corrosion or rust formation of heaters, boilers, gas fired recirculating air furnaces or heaters, or gas water heaters.

Storage stability

Shelf life: Use within 360 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
1,1,1,2-Tetrafluoroethane	US WEEL	TWA	1,000 ppm

Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Eye protection should not be necessary. For fabrication operations safety glasses (with side shields) are recommended. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

Skin protection

Hand protection: Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

Other protection: No precautions other than clean body-covering clothing should be needed.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In dusty or misty atmospheres, use an approved particulate respirator. When respiratory protection is required for certain operations, including but not limited to saw, router or hot-wire cutting, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	Board
Color	Blue
Odor	None
Odor Threshold	Odorless
pH	Not applicable
Melting point/range	90 - 130 °C (194 - 266 °F) <i>Estimated.</i>
Freezing point	Not applicable
Boiling point (760 mmHg)	Not applicable
Flash point	closed cup Not applicable
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	May form combustible dust concentrations in air during processing, handling or other means.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	Not applicable
Relative Density (water = 1)	0.027 - 0.064 <i>Estimated.</i>
Water solubility	Insoluble in water
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	354 °C (669 °F) <i>ASTM D1929</i>
Decomposition temperature	No test data available
Kinematic Viscosity	Not applicable
Explosive properties	No
Oxidizing properties	No
Molecular weight	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Avoid temperatures above 300°C (572°F) Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

Incompatible materials: Avoid contact with oxidizing materials. Avoid contact with: Aldehydes. Amines. Esters. Liquid fuels. Organic solvents.

Hazardous decomposition products: Does not normally decompose. Evolution of small amounts of hydrogen halides occur when heated over 250°C (482°F). Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aromatic compounds. Aldehydes. Ethylbenzene. Hydrogen halides. Polymer fragments. Styrene. Under high heat, non-flaming conditions, small amounts of aromatic hydrocarbons such as styrene and ethylbenzene are generated.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Swallowing is unlikely because of the physical state. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Acute dermal toxicity

Skin absorption is unlikely due to physical properties.

As product: The dermal LD50 has not been determined.

Acute inhalation toxicity

Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation.

Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

The LC50 has not been determined.,

Skin corrosion/irritation

Essentially nonirritating to skin.

Mechanical injury only.

Serious eye damage/eye irritation

Solid or dust may cause irritation or corneal injury due to mechanical action.

Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

Sensitization

Relevant data not available.

For respiratory sensitization:

Relevant data not available.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Additives are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency.

Carcinogenicity

Relevant data not available.

Teratogenicity

Contains a component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency

Reproductive toxicity

Contains a component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency

Mutagenicity

Relevant data not available.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

2-Propenenitrile, polymer with ethenylbenzene

Acute oral toxicity

LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity

For similar material(s): LD50, Rabbit, > 2,000 mg/kg Estimated.

Styrene, polymers

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

1,1,1,2-Tetrafluoroethane

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

Persistence and degradability

Biodegradability: Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

Bioaccumulative potential

Bioaccumulation: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

Mobility in soil

In the terrestrial environment, material is expected to remain in the soil.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Landfill. Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code
Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Combustible dust

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

The product meets the definition of an article and is exempt from inventory requirements.

16. OTHER INFORMATION

Revision

Identification Number: 37516 / A001 / Issue Date: 07/30/2018 / Version: 12.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

TWA	8-hr TWA
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International

Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US

**STYROFOAM™ CAVITYMATE™ 3.00 X 16 Inch Butt Edge Cavity Wall Extruded
Foam Insulation**

WARNING

Hazards: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Refer to the Safety Data Sheet before use.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2030 DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

**EMERGENCY TELEPHONE
NUMBER**

24-Hour Emergency Contact:

CHEMTREC +1 800-424-9300

Local Emergency Contact:

800-424-9300

Customer Information Number:

800-258-2436



©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Revision

Identification Number: 37516 / A001 / Issue Date:
07/30/2018 / Version: 12.0