



EMSEAL Joint Systems, Ltd.
25 Bridle Lane, Westborough, MA 01581 USA
www.emseal.com

Safety Data Sheet

SEISMIC COLORSEAL

Preparation Date March 15, 2015 Revision Date May 31, 2015

1. Identification of the Substance / Preparation

Product identifier	SEISMIC COLORSEAL
Other identifier or names	COS Foam
UN ID number	None
Manufacturer Address	EMSEAL LLC 120 Carrier Drive Toronto, Ontario M9W 5R1 Canada
Company Phone	(508) 836-0280 M-F 9am - 5pm
Emergency Phone	CHEMTREC (800) 424-9300 (24 Hours)
CHEMTREC International Phone	+1 703-527-3887 (24 Hours)

2. Hazardous Identification

Hazardous Classification	This product is not classified as hazardous when used as intended.
Signal Word	None
Pictograms	None
Emergency Overview:	No emergency requirements.

3. Composition / Information on Ingredients

EMSEAL SEISMIC COLORSEAL is composed of polyurethane foam impregnated with a proprietary solid acrylic polymer bonded to a fully cured silicone sealant. It is classified as Non-Hazardous.

NOTE: Silicone facing is fully cured. The composition of the silicone in its liquid state is comprised of the following:

Chemical Name	CAS #	% by Weight
Titanium Dioxide	13463-67-7	1 - 5
Methylvinyl bis(N-thylacetamido) silane	87855-59-2	1 - 5
Antimony nickel titanium oxide yellow	8007-18-9	1 - 5
Dimethyl, methylhydrogen siloxane, dehydrogenated reaction with hydroxydiethylamine	68952-53-4	1 - 5
Carbon black	1333-86-4	0.1 - 1
Quartz	14808-60-7	0.1 - 1
Cobalt titanate green spinel	68186-85-6	0.1 - 1
N-ethylacetamide	625-50-3	0.1 - 1
Octamethylcyclotetrasiloxane	556-67-2	0.1 - 1



4. First Aid Measures

- 4.1 EYES:** Flush with water for at least 15 minutes, and call physician if problems persist.
- 4.2 SKIN:** Product may leave a sticky residue, and mild irritation if prolonged exposure. Scrub with soapy water until adhesive is removed.
- 4.3 INGESTION:** Do not eat – call physician if ingested.

5. Fire-fighting Measures

- 5.2 FLAMMABILITY:** Slight. Material can support an open flame or smoldering ignition. The foam can melt while burning which can contribute fire to spread.
- 5.2 FLASH POINT:** Unknown.
- 5.3 AUTO-IGNITION TEMPERATURE:** Unknown.
- 5.4 EXTINGUISHING MEDIA:** Large volumes of water, or ABC chemical may be appropriate for initial control or small volumes of impregnated foam.
- 5.5 HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon di/mon oxides will be formed as well as other noxious and toxic fumes upon combustion – do not breath combustion products.

6. Accidental Release Measures

If material is unusable pick up pieces and dispose of in accordance with local regulations; material and all components are non-toxic and normal landfill will most often be acceptable.

7. Handling and Storage

Store in original packaging below 35°C. There are no special handling instructions.

8. Exposure Controls / Personal Protection

- 8.1 RESPIRATORY PROTECTION:** Not required
- 8.2 EYE PROTECTION:** Not required
- 8.3 SKIN PROTECTION:** Gloves of any material are suitable if desired, but not required. No other protection is required.

9. Physical and Chemical Properties

- 9.1 APPEARANCE:** Dark grey / charcoal colored foam and colored silicone with product identifying packaging.
- 9.2 ODOR:** Slight characteristic odor.
- 9.3 PERCENT SOLIDS BY WEIGHT:** 100%
- 9.4 PHYSICAL STATE:** Solid
- 9.5 PERCENT VOLATILE:** <1% wt/wt
- 9.6 DENSITY:** 0.4g/cm³
- 9.7 DECOMPOSITION:** > 300°C
- 9.8 SOLUBILITY IN WATER:** None



10. Stability and Reactivity

Stable under normal conditions – avoid temperatures in excess of 300°C, strong acids and bases, and open flame.

11. Toxicological Information

Unknown.

12. Ecological Information

Unknown

13. Disposal Considerations

No known hazard. Dispose of in accordance with local regulations; material and all components are non-toxic and disposal in normal landfill will most often be acceptable.

14. Transportation Information

Not hazardous – safe for non-hazardous shipping.

15. Regulatory Information

Unknown.

16. Other Information

No other information provided.

This page has been left blank.