

Core Lock Double Rebar Positioner



MATERIAL CONFORMANCE

ASTM A82 / A82M - (Cold drawn steel wire)
 Tensile Strength - 80,000 psi
 Yield Point - 70,000 psi
ASTM A951 / A951M-06 - (Standard Specification for Steel Wire for Masonry Joint Reinforcement)
ACI / ASCE 530 - (Building code requirements for masonry structures)
 Mill Galvanized / Zinc Coating: **ASTM A641 / A641M (0.10 oz per sq ft)**
 Hot Dip Galvanized after fabrication / Zinc Coating
ASTM A153 / A153M-B2 (1.50 oz per sq ft)
 Stainless Steel **ASTM 580 / ASTM 580M Type 304** (Type 316 available on special order)

WIRE Recycled Content:
 Mill Galvanized & Hot Dip,
 82.8% Post-Consumer
 17% Post Industrial / Pre - Consumer
 Stainless Steel,
 60% Post Consumer
 V O C Content - 0%



DESCRIPTION / SIZES / FINISHES

DESCRIPTION:

- CoreLock is installed 1-1/4" deep into the CMU instead of on top of the block.
- Diagonal positioning in the core ensures that rebar is always centered automatically and prevents any movement.
- Does not interfere with installation of wire reinforcement.
- One piece design with no welds.
- Safety bend ensures correct installation.

SIZES:

8" Ø ~ à^ F€ Double 12" Ø ~ à^
 1 1/4" Double

FINISHES: Mill Galvanized U@!