


CONTROL JOINTS ALTERNATE A

MICHIGAN CONTROL JOINT (# 15 LB FELT)



MASONPRO, Inc.
43300 Seven Mile Road
Northville, MI 48167
1-800-659-4731

Asphalt Saturated Organic Felts

Asphalt Saturated Organic Felts are manufactured from premium quality organic mat and saturated with high-grade asphalt.

Usage

Asphalt Saturated Organic Felts are designed as an underlayment product to be applied over the roof deck prior to the installation of asphalt shingles. Install Asphalt Saturated Organic Felts as a secondary barrier to moisture caused by wind-driven rain and ice damming.

Products

15# ASTM SPECIFICATION FELT

- ◆ Meets ASTM D 226, Type I
- ◆ Dimensions: 144' X 36"
- ◆ Coverage per Roll: 4 Squares
- ◆ Approx. Sq. Ft. per Roll: 432 Sq. Ft.
- ◆ Also available in 3 Square Roll

30# ASTM SPECIFICATION FELT

- ◆ Meets ASTM D 226, Type II
- ◆ Dimensions: 72' X 36"
- ◆ Coverage per Roll: 2 Squares
- ◆ Approx. Sq. Ft. per Roll: 216 Sq. Ft.
- ◆ Also available in 18" Split (108 Sq. Ft.) Roll

PRO 15 SPECIFICATION FELT

- ◆ Meets ASTM D 4869, Type I
- ◆ Dimensions: 144' X 36"
- ◆ Coverage per Roll: 4 Squares
- ◆ Approx. Sq. Ft. per Roll: 432 Sq. Ft.

NO 15 SPECIFICATION FELT

- ◆ Meets ASTM D 4869, Type I
- ◆ Dimensions: 144' X 36"
- ◆ Coverage per Roll: 4 Squares
- ◆ Approx. Sq. Ft. per Roll: 432 Sq. Ft.
- ◆ Also available in 3 Square Roll

NO 15 NON-SPEC FELT

- ◆ Dimensions: 144' X 36"
- ◆ Coverage per Roll: 4 Squares
- ◆ Approx. Sq. Ft. per Roll: 432 Sq. Ft.

PRO 30 SPECIFICATION FELT

- ◆ Meets ASTM D 4869, Type II
- ◆ Dimensions: 72' X 36"
- ◆ Coverage per Roll: 2 Squares



NO 30 SPECIFICATION FELT

- ◆ Meets ASTM D 4869, Type I
- ◆ Dimensions: 72' X 36"
- ◆ Coverage per Roll: 2 Squares
- ◆ Approx. Sq. Ft. per Roll: 216 Sq. Ft.
- ◆ Also available in 18" Split (108 Sq. Ft.) and Jumbo (180 Sq. Ft.) Rolls

NO 30 NON-SPEC FELT

- ◆ Dimensions: 72' X 36"
- ◆ Coverage per Roll: 2 Squares
- ◆ Approx. Sq. Ft. per Roll: 216 Sq. Ft.






Storage and Handling

Asphalt Saturated Organic Felts require protection from damage and the weather. Store rolls upright in a dry location and never install when wet or over a wet roof deck.



Warranty

 Warranted to be free from manufacturer's defects.



Note

 All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty or responsibility of any kind, expressed or implied, except as may be indicated otherwise in this literature.

MASONPRO, Inc
43300 Seven Mile Road
Northville, MI 48167
1-800-659-4731
www.masonpro.com



Tarco

One Information Way, Suite 225
Little Rock, AR 72202
Voice: 501-945-4506 ♦ 800-365-4506
Fax: 501-945-7718 ♦ www.tarcoroofing.com

