

Product Data Sheet

Core Lock Single Rebar Positioner



MATERIAL CONFORMANCE

Wire (Carbon Steel): Prefabricated from cold-drawn steel wire conforming to **ASTM A1064/A1064M, ASTM A82/ A82M**

Tensile Strength - 80,000 p.s.i. | Yield Point - 70,000 p.s.i. minimum

ASTM A951/A951M (Standard Specification for Steel Wire for Masonry Joint Reinforcement)

ACI / ASCE 530 (Building Code Requirements for Masonry Structures)

Hot-Dip Galvanized after fabrication: **ASTM A153/A153M-B2 (1.5 oz/ft)**

Wire (Stainless Steel): **ASTM A580/ASTM 580M - AISI Type 304**
(Type 316 available on special orders)



Recycled Content:

Hot Dipped,
82.8% Post-Consumer
17% Post Industrial / Pre - Consumer
Stainless Steel,
97% Pre-Consumer
V O C Content - 0%

DESCRIPTION / SIZES / FINISHES

DESCRIPTION:

- CoreLock is installed 1-1/4" deep into the CMU instead of on top of the block.
- Diagonal positioning in the core ensures that rebar is always centered automatically and prevents any movement.
- Does not interfere with installation of wire reinforcement.
- One piece design with no welds.
- Safety bend ensures correct installation.

SIZES:

6" Single 8" Single 10" Single 12" Single
1 1/4" x 1/4" x 1/4" 1 1/4" x 1/4" x 1/4"

FINISHES: Mill Galvanized Uco!Á