Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

1/7 Issue Date: 10/18/19

CECTION 1. Identification		
SECTION 1: Identification	Delensered and (DD)	
GHS Product Identifier:	Polypropylene (PP)	
Product Form:	Pellets/ Resin	
Other means of Identification:	Polypropylene Impact Copolymer Product Series 2000, 3000, 4000, & 8000	
Recommended use of the chemical and restrictions on use:	Industrial applications/ Manufacture of plastic articles	
Supplier Details:		
Company Name:	Mortar Net Solutions	
Company Address:	6575 Daniel Burnham Drive Suite G	
. ,	Portage, Indiana 46368	
	ph (800)-664-6638 fax 219-757-5088	
Email address of responsible	www.mortarnet.com	
person:		
Emergency Telephone Number:	CHEMTREC: (800)-424-9300	
Section 2: Hazard Identification		
Classification of substance or mix		
Classification (GHS – US)	Combustible Dust	
Label Elements		
Signal Word (GHS – US)	Warning	
Hazard Statements (GHS – US)	May form combustible dust concentration is air during processing and handling.	
Precautionary Statements Prevention:	Net Applicable	
Response:	Not Applicable Not Applicable	
Storage:	Not Applicable	
Disposal:	Not Applicable	
Additional Label Elements	This production contains no substances subject to the reporting or planning requirement of SARA Title III.	
	Dust can irritate eyes.	
	Pellets may present a slipping hazard.	
	Melted polymer may stick to skin creating burns.	
	Static charges and discharges may be produced during product transfer.	
	Base polymer contains the elements hydrogen and carbon.	
Section 3: Composition/ inforn		
Substance/ Mixture:	Polymer	
Common Name and Synonyms:	Polypropylene Block Copolymer Product Series 2000, 4000, 3000 & 8000	
CAS Number:	9010-79-1	
Product Code:	2000, 3000, 4000, & 8000	
	2000, 3000, 4000, & 8000	

Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

2/7 Issue Date: 10/18/19

Ingredient Name	%	CAS Number
Propene, polymer with ethylene	> 99	9010 - 79 - 1
Proprietary Stabilizers	<1	Trade Secrets

Polypropylene Resin/Pellets

Section 4: Fi	rst Aid Measures			
	f necessary first aid	measures		
Inhalation:	If there is excessive inhalation of fumes move person to fresh air. Get medical attention if symptoms continue.			
Skin Contact:	If material is molten, do not pull molten polymer from skin. Cool with water. Get medical attention if burn is			
	severe.			
Eye Contact:		If material is molten cool with water and get medical attention. If material is dust rinse with water and get medical attention if symptoms persist.		
Ingestion:	Remove material fro	om mouth. Rinse mouth with water.		
Most importa	nt symptoms and ef	ffects, both acute and delayed		
Inhalation:	Nuisance dusts can heated.	be irritating to the upper respiratory tract. Irritating fume may form when the material is		
Skin Contact:	Contact with hot or	molten material may cause thermal burns to the skin.		
Eye Contact:	Dust from processing thermal burns.	ng may cause irritation to the eyes. Contact to the eyes with molten material may cause		
Ingestion:	Swallowed materia hazard.	I should pose no hazard, but get medical attention if symptoms occur. May be a choking		
Indication of a		ical attention and special treatment needed		
	ormation available.			
Section 5: Fi	refighting Measure	25		
Extinguishing	media			
Suitable extingu	uishing media:	Dry chemical extinguisher, carbon dioxide extinguisher, water spray/ mist		
Unsuitable exti	nguishing media:	Do not use solid stream or jet. May cause fire to spread.		
Special hazard	ds arising from the c			
Fire hazard:		May be combustible at high temperatures. May form combustible dust concentration in air		
Explosion hazard:		Dust explosion hazard. Airborne dust that is exposed to an ignition source may burn in oper areas or explode in confined spaces.		
Hazardous decomposition products Release of carbon dioxide, carbon m in case of fire:		Release of carbon dioxide, carbon monoxide, and hydrocarbons.		
Advice for fire	efighters			
Firefighting instructions:		Remove all nonessential personnel from area. Do no use high pressure stream/ jet to extinguish fire. Be careful not to raise flammable dust during firefighting measures.		
Protection duri	ng firefighting:	Self – contained breathing apparatus and protective firefighting clothing (bunker gear)		
should be worn if fighting the fire at a close proximity.Other information:Hot material may reignite, keep material wet until cooled.				

Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

3/7 Issue Date: 10/18/19

Section 6: Accidental Releas	e Measures		
Personal precautions, protective	e equipment and emergency procedures		
For non – emergency personnel:	Spilled material may create a slipping hazard. Remove material from walking/ working surfaces immediately.		
For emergency responders:	Protective clothing may be necessary in certain incidents – see Section 8 for further information		
Environmental precaution:	Recycle if possible. Do not dispose of this material into the environment. Do not allow material to enter public waterways.		
Methods and materials for con	tainment and clean up		
Small Spill:	Vacuum, sweep and shovel material into suitable containers. Recycle or dispose of in accordance with local, state and federal laws.		
Large Spill:	Prevent spread of material. Vacuum, sweep and shovel material into suitable containers. Recycle or dispose of in accordance with local, state and federal laws. Inform local authorizes of any spread into sewage or open bodies of water. Avoid creating large amounts of dust in confined areas.		

Polypropylene Resin/Pellets

Section 7: Handling and Stora	ge
Precautions for safe handling	
Protective Measures:	Maintain good housekeeping. Avoid spills and potential slipping hazards caused by pellets. Employees may be exposed to engulfment hazards when handling bulk materials. Do not store material near flammable substances. Provide adequate ventilation and dust control measures. Ground and bond transfer equipment and storage containers to dissipate static charges. Do not breathe gas, fumes, or vapors from this product. Wear protective clothing when handling hot or molten material.
Hygiene Measures:	Do not eat, drink or smoke while handling material. Wash hands and face after handling material.
Conditions for safe storage, including any incompatibilities	Avoid storing material near flammable materials. Keep away from strong oxide agents. Store in clean dry areas away from direct sunlight. Ground/ bond containers and transfer equipment.

Section 8: Exposure controls/personal protection

cupational exposure limits		
Ingredient Name	Exposure Limits	
Polypropylene (PP) Resin/ Pellets	ACGIH TLV (United States).	
	Particulates Not Otherwise Specified	
	TWA: 10 mg/m ³ 8 hours. Form: Inhalable	
	Particulates Not Otherwise Specified	
	TWA: 3 mg/m ³ 8 hours. Form: Respirable fraction	
	OSHA PEL (United States).	
	Particulates Not Otherwise Specified	
	TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction	
	Particulates Not Otherwise Specified	
	TWA: 15 mg/m ³ 8 hours. Form: Total	

Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

4/7 Issue Date: 10/18/19

Exposure Controls	
Appropriate engineering controls	Work area should have adequate ventilation. If dust generation occurs during processing, local ventilation should be provided to prevent exposure.
Environmental exposure controls	Ventilation of dust must comply with local, state and federal regulation.
Individual protection measures	
Hand protection	Use proper hand protection when handling hot or molten material to prevent thermal burns.
Eye/ face protection	Safety glasses. Face shield may be need when handling hot or molten material to prevent thermal burns.
Skin and body protection	Wear proper protective clothing.
Respiratory Protection	Respiratory protection may be needed when handling material in areas that do not have adequate ventilation, or if vapors or fumes are present.

Section 9: Physical and Chemical Properties

Information on basic physical and chemical properties		
Physical State	Solid	
Appearance	Pellets/Resin	
Color	Translucent, opaque, or white	
Odor	Odorless	
Odor Threshold	No data available	
рН	No data available	
Melting Point	144° C to 165° C	
Boiling Point	No data available	
Flash Point	No data available	
Evaporation Rate	No data available	
Flammability (solid, gas)	No data available	
Lower and up flammability or explosive limit	No data available	

Polypropylene Resin/Pellets

Vapor pressure	No data available	
Vapor density	No data available	
Relative density	No data available	
Solubility	Insoluble in water	
Partition coefficient: n-octanol/water	Insoluble in water and octanol	
Auto ignition temperature	> 340° C	
Decomposition temperature	>300° C	
Possibility of hazardous reactions	No data available	
Conditions to Avoid	Strong Oxidizing agents	
Incompatible materials	Strong Oxidizing agents	
Hazardous decomposition products	No data available	

Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

5/7 Issue Date: 10/18/19

Section 10: Stability and R	Peactivity			
Reactivity	No data available related to reactivity for this product or its ingredients			
Chemical stability	The product is stable			
Possibility of hazardous reaction		Dust		
-	may form explosive mixture in air.			
Conditions to Avoid	Avoid dust formation/accumulation. Dust can cause eye irritation and explosive mix	xture		
	in air. Avoid buildup of static charges. Heat, open flames, sparks and direct sunl	light.		
	Vapors or fumes can cause respiratory tract irritation.			
Incompatible materials	Strong Oxidizing agents			
Hazardous decomposition prod		xide,		
Section 11:Toxicological In	carbon dioxide, toxic fumes.			
Information on the likely routes				
exposure				
Acute Toxicity	Not classified			
Skin or eye absorption	Exposure to dusts may cause eye irritation			
Inhalation	Exposure to dusts, fumes or vapors may cause respiratory tract irritation.			
Ingestion	No known effects or hazards			
Carcinogenicity	Not classifiable as to its carcinogenicity to humans			
Reproductive toxicity	Not classified			
Specific target organ toxicit	ity Not classified			
(single/repeat)				
Aspiration hazard	Not classified			
Section 12: Ecological Info	Section 12: Ecological Information			
Ecotoxicity Wildlife, especially small fish may digest pellets. Pellets are not toxic, but may block the digestiv				
tract and cause starvation or death.				
Persistence and degradability Biologically non-degradable. Degrades under long term exposure to sunlight and/or heat				
Bioaccumulative potential	Not known to be bio-accumulative			
Mobility in soil Other adverse effects				
Section 13: Disposal considerations Disposal Methods This product does not meet the RCRA criteria of a hazardous waste. Product can				
recycled. Disposal should only be considered if no further recycling is possible. Dispo				
accordance with local, state, and federal regulations.		30 111		
Section 14: Transport info				
UN Number	Not regulated			
UN Proper shipping name Not regulated				
Transport Hazard class(es)				
Packing group, if applicable	Not regulated			
Marine pollutant (Yes/No)	No			

Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

Polypropylene Resin/Pellets

6/7 Issue Date: 10/18/19

Polypropylene Resin/Pellets			
Special precautions which a user			
needs to comply with in connect	·		
conveyance either within or outs	ide their premises		
Section 15: Regulatory Info	prmation		
U.S. Federal Regulations			
TSCA	All components of this product are listed or exempted from the United States		
	Environmental Protection Agency Toxic Substances Control Act inventory.		
SARA 302/304	No products were found		
SARA 311/312	Fire Hazard		
SARA 313	This product contains no exceedance of chemical concentration that are subject to the		
	reporting requirements of section 313 of Title III of the Superfund Amendments and		
	Reauthorization Act of 1986 and 40 CFR Part 372.		
California Proposition 65	While Pinnacle Polymers ("Pinnacle") has not tested for the presence of California		
	Proposition 65 ("Proposition 65") substances, our products are not known to contain cancer-causing chemicals as designated by Proposition 65. Pinnacle's products may		
	contain residual levels of n-hexane, which has been identified by the State of California		
	as a potential cause of birth defects or other reproductive harm. Pinnacle does not		
	believe that any residual level of n-hexane in articles produced from Pinnacle's polypropylene exceeds the Maximum Allowable Dose Levels ("MADLs"). Nonetheless,		
	proper ventilation, consistent with good manufacturing practices, should be used		
	always during the melt processing of polypropylene.		
Canada	All components of this product are listed or exempted from DSL (Domestic Substances		
	List)		
Europe	Not Known to contain substances of very high concern (SVHC). ROHS Compliant.		
Section 16: Other Informat	ion		
Hazardous Materials Information	n System (U.S.A.) This information is intended solely for the use of individuals trained in the		

HMIS system.

HMIS III Rating		
Health		0
Flammability		1
Physical Hazard	•••	0
Personal Protection	:	See section 8 of SDS

Health	0
Flammability	1
Physical hazards	0

National Fire Protection Association (NFPA) Ratings This information is intended solely for the use of individuals trained in the NFPA system.


Moisture Management For Masonry

Safety Data Sheet

Mortar Net SOLUTIONS

BlockFlash[™] Flashing Pans 6, 8, 10, 12 inch

7/7 Issue Date: 10/18/19



NFPA (National Fire Protection Association)			
NFPA health hazard	:	0	
NFPA fire hazard	:	1	
NFPA reactivity	•••	0	

Polypropylene Resin/Pellets

US OSHA LABEL as specified under 29 CFR §1910.1200 (f)

Polypropylene Copolymer / Block

Mortar Net Solutions 6575 Daniel Burnham Drive Suite G Portage, IN 46368 USA Tel. 800-664-6638 or 219-757-5088

Warning

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

Supplemental Information: Based on conditions common to industrial workplace use of this product

Do not store near flammable substances. Bond/ ground transfer equipment to prevent static buildup. Spilled pellets may create a slipping hazard. Sweep up spillage and dispose of properly. Skin or eye contact with hot polymer can cause thermal burns. Processing the polymer at high temperatures may form vapors that irritate the eyes and respiratory tract.

The information contained herein is accurate to the best of our knowledge. Mortar Net Solutions makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances.